

Quotation

To

Company : Siemens AG
City / Country : Duisburg / Germany
Name : Stoverink Simon
Dept :
Tel :
Fax :
E-mail :

Name : N. HOST
Dept : Sales Dept.
Tel : +33 (0)3 69 20 51 50
Fax : +33 (0)3 88 67 60 75
E-mail : nhost@flender-graff.com
Page(s) : 19
Copy :
Date : 16.03.2016

Y/ref : Khursaniyah Al Fadhili - D43-K-1801 -
O/ref : D41104 quotation number 3

In response to your inquiry referenced above, we are pleased to confirm our quotation as follows :

ITEM A 1 : Flender Graffenstaden (FG) High Speed increaser, model **TX50/4C**

- *Rating conditions :* Rated power at **6800 kW**
Driven by a electric motor at **1800.0 rpm** (specified : 1800.0 rpm)
Driving a centrifugal compressor at **7309.1 rpm** (specified : 7285.0 rpm)
Service factor **1.45** according to **API613/03** (required : > 1.4)
- *Technical description :* Double helical
Manufacturing according to API standard
Flange on LS shaft end
Flange on HS shaft end
Estimated Weight : 4000 kg
- *Bearings description :* 2 cylindrical bearings on LS shaft
2 offset bearings on HS shaft
1 double acting tilting pad thrust bearing on low speed shaft non driven end
- *Mechanical running test :* Full speed, no load test during 4 hours according to the API 613 5th Edition standard.
- *Lubrication conditions :* 164 l/min of Oil ISO VG 46 at 60°C and 2.5 bar at inlet (calculated values only)
- *Miscellaneous:* Efficiency at full load : 99.03 %
Power losses at full load : 66 kW (calculated value only)
Anticipated Sound Pressure Level: 82.0 ± 2dB(A) at 1 meter

Base price : **117 900 EUR** each gear box
Delivery time : **36 weeks** after the FG acknowledgement of the order
Quantity : **8 gearboxes**

Comments :

- Coupling data taken into account on HS Shaft:
 - o Weight: 26.6 kg
 - o Center of gravity position from shaft end: 30.9 mm
 - o Inertia: 0.266 kgm²
- Coupling data taken into account on LS Shaft:
 - o Weight: 87.5 kg
 - o Center of gravity position from shaft end: 40.9 mm
 - o Inertia: 0.875 kgm²

Including :

- Customer witness of test
- After test disassembly and inspection
- Noise level test report
- Lateral analysis undamped
- Documentation : downloadable electronic file in english

Instrumentation (see the complete package on additional technical data sheet):

- *Temperature package*
12 RTD's PT100 Duplex 3 wires from Thermo Electric Company Inc.
(2 per bearing and thrust bearing side) not wired with terminal heads..... Price included
- *Bently Nevada vibration package*
8 radial (4 per shaft) & 2 axial (on LS shaft) vibration probes, 2 accelerometers (1 per shaft), 2
keyphasors (1 per shaft) not wired Price included

Spare parts (Prices are net valid only if spares are ordered together with the gearbox):

- *Commissioning Spares*
2 RTD's, 2 BN vibration probes, 2 BN accelerometers 7 900 EUR Lot Net
- *2 Years Normal Operation Spares*
2 set of bearings with RTD's, 1 set of oil seals 48 420 EUR Lot Net
- *Strategic Spare Parts*
One complete set of rotating elements consisting of one pinion and one gear.
Tested if ordered together with the main gearbox according to API613/03
Full Speed, No Load, with Test Report..... 51 500 EUR Lot Net
- *Container for horizontal spare rotors storage painted according FG standard..... 17 100 EUR Lot Net*

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No. 41104 Item No. A
P.O. No. _____ Date _____
Requisition No. _____
Inquiry No. _____
Revision 1 Date 06.03.2015 By HNI

1	Applicable To: ☒ Proposal ☐ Purchase ☐ As Built	☐ US Standards (1.7) ☒ ISO Standards (1.7)
2	For <u>Siemens AG Dulsburg</u>	Manufacturer <u>FLENDER-GRAFFENSTADEN</u>
3	Site <u>Khursanlyah Al Fadhill</u>	Model No. <u>TX50/4C</u>
4	Unit <u>STC-SV 08-4-A</u>	Serial No. _____
5	Service <u>EM/CC</u>	Driver type <u>electric motor</u>
6	No. required <u>9</u>	Driven equipment <u>centrifugal compressor</u>
7		
8	NOTE : Numbers within () refer to applicable API standard 613 paragraphs	
9	☐ Information to be completed by purchaser ☐ Information to be completed by manufacturer	
10	○ UNITS OF MEASUREMENT	■ BASIC GEAR DATA
11	☐ US Customary units	
12	☒ SI units	
13	○ RATING REQUIREMENTS	
14	Driven equip. (2.1.4): Norm. _____ Max _____ kW	☒ Single stage ☐ Single helical
15	Driver: Rated _____ Max _____ kW	☐ Double stage ☒ Double helical
16	Normal transmitted power (2.2.2) _____ kW	☐ Epicyclic ☐ horizontal offset
17	Gear unit rated power (2.2.1) <u>6800</u> kW	Mechanical rating (1.5.16) <u>9520</u> kW @ <u>1800 / 7309,1</u> rpm
18	Torque @ max cont speed _____ Nm	Gear service factor (2.2.3.1) <u>1,44</u> API 613/2003 5 TH (actual)
19	Max torque (2.2.1) _____ Nm @ _____ rpm	Full load gear unit power loss <u>66</u> kW
20	☐ Reducer ☒ Increaser	Gear Unit Mechanical efficiency <u>99,03</u> %
21	Rated speed (2.1.5):	Rating speed Pinion <u>7,309,1</u> Gear <u>1,800,0</u> rpm
22	Input <u>1800</u> rpm ☐ Specified ☒ Nominal	Hardness used for
23	Output <u>7285</u> rpm ☐ Specified ☒ Nominal	Rating, (HB or Rc) Pinion <u>58 HRC</u> Gear <u>58 HRC</u>
24	Allow var in gear ratio (2.1.6) (+) (-) _____ %	Tooth pitting index, "K" (2.2.4.1) (2.2.4.2)
25	Max continuous speed (1.5) <u>1800 / 7285</u> rpm	Allowable <u>2,17</u> Actual <u>2,10</u> MPa
26	Trip speed (1.5) (2.1.7) <u>1980 / 8013,5</u> rpm	Material index number (Fig 3, Table 4) <u>3,03</u> MPa
27	Gear service factor (2.2.3.1) <u>1,4</u> API 613/2003 5 TH (min)	Bending stress number, "S _t " (2.2.5.1) (2.2.5.2)
28	Hardness (2.2.3.2) Pinion _____ Gear _____	Pinion: Allowable <u>265,4</u> Actual <u>256,0</u> MPa
29	Shaft assembly designation (2.1.10) _____ L/R	Gear: Allowable <u>265,4</u> Actual <u>240,9</u> MPa
30	HS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW	Pitch line velocity <u>77,1</u> m/s
31	LS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW	Anticipated SPL (2.1.6) <u>82</u> dB(A) @ <u>1</u> m
32	External loads (2.1.16) _____	WR ² referred to LS shaft <u>126,12</u> kgm ²
33	Other operating conditions (2.2.2) (2.6.1.3) _____	Breakaway torque <u>412</u> Nm @ LS Shaft
34		Pinion teeth hardness range <u>58 - 63 HRC</u>
35	○ INSTALLATION DATA (2.1.14)	Pinion teeth hardening method <u>CARBURIZED</u>
36	☐ Indoor ☐ Heated ☐ Under roof	☐ HS shaft separate hardness range _____
37	☒ Outdoor ☐ Unheated ☐ Partial sides	Gear teeth (rim) hardness range <u>58 - 63 HRC</u>
38	☐ Grade ☐ Mezzanine ☒ ONSHORE	Gear teeth hardening method <u>CARBURIZED</u>
39	☐ Winterization required ☐ Tropicalization required	Gear hub:
40	Electrical area (2.1.10) Class _____ Grp _____ Div _____	☒ Forged cylinder ☐ Forged & Copped ☐ Fabricated
41	Electrical area (2.1.10) Zone <u>2</u> Grp <u>IIA</u> Temp <u>T1</u> °C	Gear to Shaft fit method (2.5.3.2)
42	Max allow SPL (2.1.6) _____ dB(A) @ _____ m	☐ Integral ☐ Keyed interference ☒ Keyless interference
43	Elevation _____ m Barometer _____ kPa abs	Rim attachment (2.5.3.2) <u>FORGED GEAR WHEEL</u>
44	Range of ambient temperatures:	LS shaft hardness range <u>HB 230 - 274</u>
45	Dry bulb _____ Wet bulb _____	Journal static weight loads (2.6.6.3)
46	Normal _____ °C _____ °C	Pinion <u>128 / 42</u> kg Gear <u>942 / 707</u> kg
47	Maximum <u>82</u> °C _____ °C	Total gear unit assembled weight <u>4000</u> kg
48	Minimum <u>0</u> °C _____ °C	NOTES: _____
49	Unusual conditions ☐ Dust ☐ Fumes	_____
50	☐ _____	_____

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

■ GEAR DATA				○ COUPLINGS AND GUARDS		
	Pinion	Gear			Pinion	Gear
Number of teeth	33	134		Coupling furnished by (3.2.1)	Compr. Supplier	Compr. Supplier
Gear ratio	4,06			Mount coupling halves (3.2.2)	Compr. Supplier	Compr. Supplier
Tangential load, "Wt" (2.2.4.2)	88,155	N		Cplg. guard adapter by (3.2.3)	Gear Supplier	Gear Supplier
AGMA Geometry factor "J"	0,55	0,57		Cplg. guard furnished by (3.2.3)	Compr. Supplier	Compr. Supplier
Pitch diameter	201,56	818,44	mm	Coupling vendor (3.2.3)		
Outside diameter	214,10	827,60	mm	Vendor's model number (3.2.3)		
Root diameter	187,25	800,74	mm	Coupling weight on shaft, kg	26,6	87,5
Center groove diameter	177,00	790,00	mm	CG Inboard / outboard of shaft end	Outboard	Outboard
Normal pressure angle	20,00	deg		Hub drill template provided	☐	☐
Normal diametral pitch	4,62	in ⁻¹		■ SHAFT END DETAIL (2.5.4.2)		
Helix angle	25,00	deg		Shaft end detail specified by: ☒ Purchaser ☐ Gear vendor		
Center distance	510,00	mm		(Integral unless otherwise specified)		
Backlash min	0,34	mm		Shaft end detail if 'otherwise' specified:		
Net face width, "Fw"	260,00	mm		Tapered / Keyless	☐ ☐	☐ ☐
Pinion L/D	1,71			Tapered / 1-Key	☐ ☐	☐ ☐
Face overlap ratio	6,36			Tapered / 2-Keys	☐ ☐	☐ ☐
Transverse contact ratio	1,45			Cylindrical / 1-Key	☐ ☐	☐ ☐
AGMA 6011 service factor	2,64			Cylindrical / 2-Keys	☐ ☐	☐ ☐
Rating based on ANSI/AGMA 6011 with SF=1.0				Other <u>Flanged</u>	☒ ☐	☒ ☐
Durability Power	21442	kW		Shaft diameter	120,0	190,0 mm
Strength Power	17946	kW		(If integral flange use diameter immediately adjacent to flange)		
Tooth Surface Finish, Ra	0,4	0,4	µm	■ RADIAL BEARINGS		
Tooth Generation Process	Hobbing	Hobbing		Type	Pinion	Gear
Tooth Finishing Process	Grinding	Grinding			OFFSET / OFFSET	CYL. / CYL.
Lead modification (2.2.4.6)	☒ Not Req'd	☐ Req'd		Diameter	130 / 130	200 / 200 mm
Calculated Total Lead Mismatch		µm		Length	130 / 130	100 / 100 mm
■ SCUFFING DATA (2.2.6)				Journal velocity	49,8 / 49,8	18,8 / 18,8 m/s
Scuffing Data per ANSI/AGMA 925-A03				Loading	2,78 / 2,81	2,87 / 2,71 N/mm²
Scuffing Risk (2.2.6) <=5% (Low)	Calculation Method	AGMA925		Clearance (min-max)		mm
Composite surface roughness, α_x	0,57	µm		Span	550	mm
Specific film thickness, EHL λ_{min}	3,31	µm		Power loss each bearing	13,8 / 13,8	3,0 / 3,0 kW
Tooth temperature, θ_m	82	°C		Oil flow each bearing	42,0 / 42,0	10,0 / 10,0 l/min
Maximum contact temperature, θ_{Bmax}	101	°C		■ THRUST BEARINGS		
■ MATERIALS				Location		OPP.CPLG.SIDE
Gear casing	Steel	Oil seals	aluminium	Manufacturer	FLENDER	FLENDER
Pinion(s)	18CrNiMo7-6			Type	NO	COMB.TAP.LANDS
Gear rim(s)	18CrNiMo7-6			Size		BPK LEG 6"
HS Shaft	Integral	LS Shaft	42CrMo4	Area		11615 mm²
Radial bearings	Babbitt	Backing	Steel	Loading		1,14 MPa
Thrust bearing(s)	Babbitt	Backing	Steel	Rating		1,50 MPa
○ SHAFT END DETAIL				Int. thrust load		N
☒ Gear shaft end for coupling integral flange (2.5.4.2)				Ext. thrust load	4,050	9,200 N
☒ Pinion shaft end for coupling integral flange (2.5.4.2)				Power loss each	0,0	6,0 kW
☐ Other: WITHOUT BOLTS				Oil flow each bearing	0,0	20,0 l/min
				NOTES:		

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

SPECIAL PURPOSE GEAR UNITS API 613 FIFTH EDITION DATA SHEET SI UNITS ☐ Oil system furnished by (2.8.3) _____ ☐ Other _____ ☐ Gear vendor _____ ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) _____ ☐ ISO Grade _____ Load stage (2.2.6) 5,0 ■ MESH Mesh and windage power loss 26,4 kW Oil flow, mesh 40,0 l/min ■ LUBRICATION REQUIREMENTS Min. startup oil temperature 20,0 °C Normal oil inlet temperature 60,0 °C Maximum oil inlet temperature 65,0 °C Unit oil flow (total) 164,0 l/min Unit oil pressure 2,5 bar ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) _____ ☐ ISO Grade 46 Load stage (2.2.6) 5,0 ■ PIPING CONNECTIONS <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Service</th> <th>No.</th> <th>Size</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td>Lube oil inlet</td> <td>1</td> <td>2 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Lube oil outlet</td> <td>1</td> <td>6 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing drain *</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Vent</td> <td>1</td> <td>1,5 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing purge</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> * Casing drain is 'dead bottom' housing drain, not lube oil outlet ○ MOUNTING PLATES ☐ Gear furnished with (3.3.1.1) _____ ☐ Baseplate ☐ Soleplate ☐ Subplate(s) (3.3.2.10) _____ ☐ Mounting plates(s) furnished by (3.3.1.1) _____ ☐ Baseplate leveling (3.3.2.3) _____ ☐ Baseplate with leveling pads (3.3.2.3) _____ ☐ Baseplate suitable for column mounting (3.3.2.4) _____ ☐ Vendor review of purchaser's foundation dwgs. (2.1.13) _____ ☐ Grout type (3.3.1.2.4) _____ ○ CONTRACT DATA ☐ Test data prior to shipment _____ ☒ Progress report (5.3.3) _____ ☐ Vendor signoff of Inspector checklist (4.1.1.3) _____ ☒ Information retained for 20 years (4.2.1.1) (4.2.2.6.1) _____ ☐ Technical manual (5.3.5.4) _____ ☒ PAINTING (4.4.3.1) ☒ Flender standard RAL5015 (blue) ☒ Painting housing interior not allowed (2.3.1.14) _____ ○ SHIPMENT ☐ Steel rotor storage container (4.4.5) ☐ Shaft covers (4.4.4) _____ Contract unit Spares Export boxing ☐ Domestic boxing ☐ Outdoor storage over 6 mos. ☐ 3 years Indoor ☐ ○ ADDITIONAL REQUIREMENTS ○ VIBRATION DETECTORS RADIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 8 ☒ X-Y probes pinion bearings ☒ Coupling end ☒ Blind end ☒ X-Y probes gear bearings ☒ Coupling end ☒ Blind end ☐ Other _____ AXIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 2 ☐ Dual probes at each thrust bearing ☐ Single probe any shaft without thrust bearing ☐ Other _____ ONE EVENT PER REVOLUTION PROBE (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA Total No. 2 ☒ One on input shaft ☒ One on output shaft ☐ Other _____ ACCELEROMETER (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ No. required 2 ☒ Pinion coupling end ☒ Gear coupling end ☐ Other _____ ○ TEMPERATURE DETECTORS ☐ Dial type thermometers (3.4.2.7) _____ ☒ Type brg. temp. sensors (3.4.2.7) (2.7.1.3) PT100 ☐ RTD ☐ Thermocouple / ☐ Simplex ☒ Duplex Calibration Yes ☒ HS/LS bearings no. sensors each 2 / 2 ☒ Thrust number of sensing elements each face 2 ○ OTHER VIBRATION AND TEMPERATURE (3.4.2.5) (3.4.2.6) Other Gear vendor Oscillator demodulator supplied by ☐ ☒ Vibration monitor supplied by ☒ ☐ ☐ Vibration shutdown delay time _____ seconds Temperature monitor supplied by ☒ ☐ Oscillator demodulator J-box by ☒ ☐ Temp. sensor termination J-box by ☒ ☐ J-box type _____ Mount _____ ○ MISCELLANEOUS ☒ Undamped critical analysis report (2.6.2.1) ☐ w/ dampd rotr respsn analys rpt (2.6.2.4.3) (2.6.2.6) Torsional analysis by (2.6.5.2) ☐ Gear vendor ☒ Other ☐ Spare set of gear rotors (4.3.2.4) ☐ Gear case furnished with inlet purge connection (2.4.3) ☐ Orientation of oil inlet & drain conns. (2.4.6) ☒ Filter breather location (2.3.1.12) Prov. on upper casing ☐ Torsional device provisions (2.5.4.5) ☐ Rotor vertical storage provisions (2.5.4.8) ☐ Rotor vertical storage fixture(s) (3.6.2) ☐ Vendor service rep. on site (2.1.13)	Service	No.	Size	Type	Lube oil inlet	1	2 in.	ANSI 150 LBS	Lube oil outlet	1	6 in.	ANSI 150 LBS	Casing drain *				Vent	1	1,5 in.	ANSI 150 LBS	Casing purge				Job No. 41104 Item No. A P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision 1 Date 06.03.2015 By HNI
Service	No.	Size	Type																						
Lube oil inlet	1	2 in.	ANSI 150 LBS																						
Lube oil outlet	1	6 in.	ANSI 150 LBS																						
Casing drain *																									
Vent	1	1,5 in.	ANSI 150 LBS																						
Casing purge																									

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No. 41104 Item No. A
P.O. No. _____ Date _____
Requisition No. _____
Inquiry No. _____
Revision 1 Date 06.03.2015 By HNI

O INSPECTIONS AND TESTS (4.1)				
	Req'd	Witness	Observe	Test Log
☐ Advance notice of witness testing required (4.1.3)				
Number calendar days _____				
Shop Inspection (4.1.1)	☐	☐	☐	
Cleanliness Inspection (4.2.3.1)	☐	☐	☐	
Hardness Verification (4.2.3.3)	☒	☐	☐	☒
Dismantle-reassembly (4.3.2.3.1)	☒	☐	☐	☐
Contact Check (2.5.2.2)	☒	☐	☐	☐
Contact Check Tape Lift (2.5.2.2)	☒	☐	☐	☒
Gear accuracy check (2.5.2.1)	☒	☐	☐	☐
Double helical axial stability (2.5.2.3)	☒	☐	☐	☒
Special testing Integral forged gears (2.5.3.3)				
(testing per mutual agreement)	☐	☐	☐	☐
Residual unbalance check (2.6.6.2)	☒	☐	☐	☒
Mechanical Run Test (Main) (4.3.2)	☒	☐	☐	☒
Mechanical Run Test (Spare) (4.3.2.4)	☐	☐	☐	☐
Addl. Mechanical Tests (4.3.2.2.16)	☐	☐	☐	☐
Part or Full Load And Full Speed				
Test (4.3.3.1)	☐	☐	☐	☐
Full torque, reduced speed (4.3.3.2)	☐	☐	☐	☐
Full Torque Static Test (4.3.3.3)	☐	☐	☐	☐
Back-To-Back Locked Torque				
Test (4.3.3.4)	☐	☐	☐	☐
Sound Level Test (4.3.3.5)	☒	☐	☐	☒
Additional gear tooth test (4.2.2.8)	☐	☐	☐	☐
Use shop Lube System	☒	☐	☐	
Use Job lube system	☐	☐	☐	
Use shop Vibration Probes, Etc.	☐	☐	☐	
Use Job Vibration Probes, Etc.	☒	☐	☐	
Final Assembly, Maintenance &				
Running Clearance (4.2.1.1.e)	☒	☐	☐	☒
Oil System Cleanliness (4.2.3.2)	☐	☐	☐	
Oil System-Casing Joint				
Tightness (4.3.2.1.4)	☐	☐	☐	
Warning And Protection				
Devices (4.3.2.1.5)	☐	☐	☐	
Seismic Vibration Data (4.3.2.2.3)	☐	☐	☐	☐
Vibration, Phase Plots (4.3.2.2.12)	☒	☐	☐	☒
Oil Inlet Range test (4.3.2.2.13)	☐	☐	☐	☐
Tape recorded Vibration Data	☒	☐	☐	☒
(4.3.2.2.14) (4.3.2.2.15)	☐			Purchaser copy
NON-DESTRUCTIVE TESTING (4.2.1.2) (4.2.2.1)				
	Surface	Sub surface		Log
☐ Casing	☐	☐		☐
☒ Rot. Elements	☒	☒		☒
☒ Bearings	☒	☒		☒
☐ Other :	☐	☐		☐
(Specify)				

NOTES : _____


During start-up, gears can exhibit a transient spike reading of vibration levels that will exceed shutdown settings. Therefore a trip multiplier is recommended in the control system.

Mechanical running test duration 4 hours including

- Shaft vibration record using Job vibration probes if ordered
- Bearings temperature records
- Casing vibration measurement
- Sound level pressure measurement
- Power losses measurement at oil outlet
- Performed with oil ISO VG 32

Oil flow requirement and power losses are calculated values only, add normal safety margins for sizing heat exchangers.

PRELIMINARY MASS ELASTIC DATA



Customer : Siemens AG Duisburg
 Destination : Khursariyah Al Fadhili
 Purchaser order :
 F-G job number : D 41104A1 OL:
 Type and serial N° : TX50/4C



Power rating : 6800 kW
 Service factor : $AP16:3.03 \geq 1.4$
 Input speed : 1800 rpm
 Output speed : 7308.1 rpm
 Speed ratio : 4.06

Weight HSS : 143.5 kg
 Weight pos. from teeth middle HSS : 63.4 mm
 Inertia HSS : 0.585 Kg.m²
 Stiffness HSS : 5.916 MN/mrd
 Bearing type 1 : Offset 130 x 130
 Bearing type 2 : Offset 130 x 130
 Add. weight on brg. side 1 : 26.6 kg

Weight LSS : 1561.2 kg
 Weight pos. from teeth middle LSS : 10.5 mm
 Inertia LSS : 116.473 Kg.m²
 Stiffness LSS : 39.014 MN/mrd
 Bearing type 4 : Cylindrical 200 x 100
 Bearing type 3 : Cylindrical 200 x 100
 Add. weight on brg. side 4 : 87.5 kg



Positive direction of external
 APPAREIL.xls _ Edition du :06.03.2015
 1/1



ADDITIONAL TECHNICAL DATASHEET		Job No. <u>41104</u> Item No. <u>A</u> P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision <u>1</u> Date <u>06.03.2016</u> By <u>HNI</u>																																																		
☒ ADDITIONAL GEAR DATA		☐ TURNING GEAR (Dimensioning is preliminary !)																																																		
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Efficiency</th> </tr> <tr> <th style="width: 50%;">Percent of rated power</th> <th style="width: 50%;">Efficiency</th> </tr> <tr> <td style="text-align: center;">100%</td> <td style="text-align: center;">99,03</td> </tr> <tr> <td style="text-align: center;">75%</td> <td style="text-align: center;">98,92</td> </tr> <tr> <td style="text-align: center;">50%</td> <td style="text-align: center;">98,79</td> </tr> <tr> <td style="text-align: center;">25%</td> <td style="text-align: center;">98,08</td> </tr> <tr> <td style="text-align: center;">10%</td> <td style="text-align: center;">90,80</td> </tr> </table>		Efficiency		Percent of rated power	Efficiency	100%	99,03	75%	98,92	50%	98,79	25%	98,08	10%	90,80	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Calculation results</th> </tr> <tr> <td>Required turning speed</td> <td>_____ rpm</td> </tr> <tr> <td>Actual turning speed</td> <td>_____ rpm</td> </tr> <tr> <td>Required breakaway torque</td> <td>_____ Nm</td> </tr> <tr> <td>Actual breakaway torque</td> <td>_____ Nm</td> </tr> <tr> <td>Actual maximum torque</td> <td>_____ Nm</td> </tr> <tr> <td>Actual acceleration time</td> <td>_____ s</td> </tr> </table>		Calculation results		Required turning speed	_____ rpm	Actual turning speed	_____ rpm	Required breakaway torque	_____ Nm	Actual breakaway torque	_____ Nm	Actual maximum torque	_____ Nm	Actual acceleration time	_____ s																					
Efficiency																																																				
Percent of rated power	Efficiency																																																			
100%	99,03																																																			
75%	98,92																																																			
50%	98,79																																																			
25%	98,08																																																			
10%	90,80																																																			
Calculation results																																																				
Required turning speed	_____ rpm																																																			
Actual turning speed	_____ rpm																																																			
Required breakaway torque	_____ Nm																																																			
Actual breakaway torque	_____ Nm																																																			
Actual maximum torque	_____ Nm																																																			
Actual acceleration time	_____ s																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Losses</th> </tr> <tr> <td>Power loss at no load</td> <td>_____ kW</td> </tr> <tr> <td>Heat rejection</td> <td>_____ kcal/h</td> </tr> </table>		Losses		Power loss at no load	_____ kW	Heat rejection	_____ kcal/h	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Motor</th> </tr> <tr> <td>Supplier</td> <td>_____</td> </tr> <tr> <td>Power</td> <td>_____ kW</td> </tr> <tr> <td>Voltage</td> <td>_____ V</td> </tr> <tr> <td>Frequency</td> <td>_____ Hz</td> </tr> <tr> <td>Speed</td> <td>_____ rpm</td> </tr> <tr> <td>Electric standard</td> <td>_____</td> </tr> </table>		Motor		Supplier	_____	Power	_____ kW	Voltage	_____ V	Frequency	_____ Hz	Speed	_____ rpm	Electric standard	_____																													
Losses																																																				
Power loss at no load	_____ kW																																																			
Heat rejection	_____ kcal/h																																																			
Motor																																																				
Supplier	_____																																																			
Power	_____ kW																																																			
Voltage	_____ V																																																			
Frequency	_____ Hz																																																			
Speed	_____ rpm																																																			
Electric standard	_____																																																			
☐ PUMP DETAILS (Dimensioning is preliminary !)		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Turning gear</th> </tr> <tr> <td>Type</td> <td>_____</td> </tr> <tr> <td>Ratio</td> <td>_____</td> </tr> </table>		Turning gear		Type	_____	Ratio	_____																																											
Turning gear																																																				
Type	_____																																																			
Ratio	_____																																																			
Design : _____ Speed : _____ rpm Oil flow : _____ l/min Oil pressure : _____ bar NPSH : _____ m Safety valve : _____ Driving method : _____ Material : _____ Flanges : _____ Testing : _____ Furniture of ATEX certificate : _____		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Clutch</th> </tr> <tr> <td>Type</td> <td>_____</td> </tr> <tr> <td>Max. allowable torque</td> <td>_____ Nm</td> </tr> </table>		Clutch		Type	_____	Max. allowable torque	_____ Nm																																											
Clutch																																																				
Type	_____																																																			
Max. allowable torque	_____ Nm																																																			
		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Miscellaneous</th> </tr> <tr> <td>Starting device</td> <td>_____</td> </tr> <tr> <td>Switch details</td> <td>_____</td> </tr> </table>		Miscellaneous		Starting device	_____	Switch details	_____																																											
Miscellaneous																																																				
Starting device	_____																																																			
Switch details	_____																																																			
☒ INSTRUMENTATION PACKAGE																																																				
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="3" style="text-align: center;">Thermometer</th> </tr> <tr> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> <tr> <td>Qty</td> <td></td> <td></td> </tr> <tr> <td>Type</td> <td></td> <td></td> </tr> </table>		Thermometer			Bearing	Thrust bearing	Oil inlet/outlet	Qty			Type			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="3" style="text-align: center;">Thermoelements</th> </tr> <tr> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> <tr> <td>Type</td> <td>DUPLEX 2x3F</td> <td>DUPLEX 2x3F</td> </tr> <tr> <td>Classification</td> <td>IEC60751</td> <td>IEC60751</td> </tr> <tr> <td>Removable from the outside</td> <td>NO</td> <td>NO</td> </tr> <tr> <td>ATEX</td> <td>ATEX Exia</td> <td>ATEX Exia</td> </tr> </table>		Thermoelements			Bearing	Thrust bearing	Oil inlet/outlet	Type	DUPLEX 2x3F	DUPLEX 2x3F	Classification	IEC60751	IEC60751	Removable from the outside	NO	NO	ATEX	ATEX Exia	ATEX Exia																			
Thermometer																																																				
Bearing	Thrust bearing	Oil inlet/outlet																																																		
Qty																																																				
Type																																																				
Thermoelements																																																				
Bearing	Thrust bearing	Oil inlet/outlet																																																		
Type	DUPLEX 2x3F	DUPLEX 2x3F																																																		
Classification	IEC60751	IEC60751																																																		
Removable from the outside	NO	NO																																																		
ATEX	ATEX Exia	ATEX Exia																																																		
Shaft vibrations																																																				
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th></th> <th>Radial</th> <th>HS</th> <th>Axial</th> <th>LS</th> <th>Keyphasor</th> <th>Accelerometer</th> </tr> <tr> <td>Type</td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td></td> <td>No</td> <td></td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td>ACCELEROMETER BENTLY</td> </tr> <tr> <td>Probe</td> <td>Yes</td> <td>HS</td> <td>No</td> <td>LS</td> <td>Yes</td> <td></td> </tr> <tr> <td>Proximitors</td> <td>Yes</td> <td>HS</td> <td>No</td> <td>LS</td> <td>Yes</td> <td></td> </tr> <tr> <td>Probe holder</td> <td>Yes</td> <td>HS</td> <td>No</td> <td>LS</td> <td>Yes</td> <td></td> </tr> <tr> <td>Connection head</td> <td>Yes</td> <td>HS</td> <td>No</td> <td>LS</td> <td>Yes</td> <td></td> </tr> <tr> <td>mounting kit</td> <td></td> <td>LS</td> <td>Yes</td> <td></td> <td></td> <td>Yes</td> </tr> </table>					Radial	HS	Axial	LS	Keyphasor	Accelerometer	Type	B.N. 3300 XL 8mm Sys. 9M		No		B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY	Probe	Yes	HS	No	LS	Yes		Proximitors	Yes	HS	No	LS	Yes		Probe holder	Yes	HS	No	LS	Yes		Connection head	Yes	HS	No	LS	Yes		mounting kit		LS	Yes			Yes
	Radial	HS	Axial	LS	Keyphasor	Accelerometer																																														
Type	B.N. 3300 XL 8mm Sys. 9M		No		B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY																																														
Probe	Yes	HS	No	LS	Yes																																															
Proximitors	Yes	HS	No	LS	Yes																																															
Probe holder	Yes	HS	No	LS	Yes																																															
Connection head	Yes	HS	No	LS	Yes																																															
mounting kit		LS	Yes			Yes																																														
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Junction box(es)</th> </tr> <tr> <td>Qty</td> <td style="text-align: center;">0</td> </tr> <tr> <td>Manufacturer</td> <td>_____</td> </tr> <tr> <td>Material</td> <td>_____</td> </tr> <tr> <td>ATEX</td> <td style="text-align: center;">None</td> </tr> </table>		Junction box(es)		Qty	0	Manufacturer	_____	Material	_____	ATEX	None	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2" style="text-align: center;">Miscellaneous</th> </tr> <tr> <td>Identification</td> <td>☒ wire ☒ conduit ☐ junction box</td> </tr> <tr> <td>Conduit type</td> <td>_____</td> </tr> <tr> <td>Transmitter type</td> <td>_____ Qty _____</td> </tr> <tr> <td>Terminal block type</td> <td>_____ Qty _____</td> </tr> </table>		Miscellaneous		Identification	☒ wire ☒ conduit ☐ junction box	Conduit type	_____	Transmitter type	_____ Qty _____	Terminal block type	_____ Qty _____																													
Junction box(es)																																																				
Qty	0																																																			
Manufacturer	_____																																																			
Material	_____																																																			
ATEX	None																																																			
Miscellaneous																																																				
Identification	☒ wire ☒ conduit ☐ junction box																																																			
Conduit type	_____																																																			
Transmitter type	_____ Qty _____																																																			
Terminal block type	_____ Qty _____																																																			

Y/ref : Khursaniyah Al Fadhili - D43-K-3801 -
O/ref : D41104 quotation number 3

ITEM B 1 : Flender Graffenstaden (FG) High Speed increaser, model **TX40/5C**

- *Rating conditions :* Rated power at **1620 kW**
Driven by a electric motor at **1800.0 rpm** (specified : 1800.0 rpm)
Driving a centrifugal compressor at **10737.9 rpm** (specified : 10736.0 rpm)
Service factor **1.47** according to **API613/03** (required : > 1.4)
- *Technical description :* Double helical
Manufacturing according to API standard
Flange on LS shaft end
Flange on HS shaft end
Estimated Weight : 1900 kg
- *Bearings description :* 2 cylindrical bearings on LS shaft
2 tilting pads bearings on HS shaft
1 double acting tilting pad thrust bearing on low speed shaft non driven end
- *Mechanical running test :* Full speed, no load test during 4 hours according to the API 613 5th Edition standard.
- *Lubrication conditions :* 64 l/min of Oil ISO VG 46 at 60°C and 2.5 bar at inlet (calculated values only)
- *Miscellaneous:* Efficiency at full load : 98.70 %
Power losses at full load : 21 kW (calculated value only)
Anticipated Sound Pressure Level: 82.0 ± 2dB(A) at 1 meter

Base price : **103 850 EUR** each gear box

Delivery time : **36 weeks** after the FG acknowledgement of the order

Quantity : **1 gearbox**

Comments :

- Coupling data taken into account on HS Shaft:
 - o Weight: 10.4 kg
 - o Center of gravity position from shaft end: 28.2 mm
 - o Inertia: 0.104 kgm²
- Coupling data taken into account on LS Shaft:
 - o Weight: 26.4 kg
 - o Center of gravity position from shaft end: 30.9 mm
 - o Inertia: 0.264 kgm²

Including :

- Customer witness of test
- After test disassembly and inspection
- Noise level test report
- Lateral analysis undamped
- Documentation : downloadable electronic file in English

Instrumentation (see the complete package on additional technical data sheet):

- *Temperature package*
12 RTD's PT100 Duplex 3 wires from Thermo Electric Company Inc.
(2 per bearing and thrust bearing side) not wired with terminal heads..... Price included
- *Bently Nevada vibration package*
8 radial (4 per shaft) & 2 axial (on LS shaft) vibration probes, 2 accelerometers (1 per shaft), 2 keyphasors (1 per shaft) not wired Price included

Spare parts (Prices are net valid only if spares are ordered together with the gearbox):

- *Commissioning Spares*
2 RTD's, 2 BN vibration probes, 2 BN accelerometers 7 900 EUR Lot Net
- *2 Years Normal Operation Spares*
1 set of bearings with RTD's, 1 set of oil seals 26 010 EUR Lot Net
- *Strategic Spare Parts*
One complete set of rotating elements consisting of one pinion and one gear.
Tested if ordered together with the main gearbox according to API613/03
Full Speed, No Load, with Test Report..... 37 100 EUR Lot Net
- *Container for horizontal spare rotors storage painted according FG standard*..... 15 850 EUR Lot Net

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

1 Applicable To: ☒ Proposal ☐ Purchase ☐ As Built 2 For <u>Siemens AG Dulsburg</u> 3 Site <u>Khursaniyah Al Fadhlili</u> 4 Unit <u>STC-SV 06-3-A</u> 5 Service <u>EM/CC</u> 6 No. required <u>1</u>	Job No. <u>41104</u> Item No. <u>B</u> P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision <u>1</u> Date <u>06.03.2015</u> By <u>HNI</u> ☐ US Standards (1.7) ☒ ISO Standards (1.7)
7 NOTE : Numbers within () refer to applicable API standard 613 paragraphs 8 ☐ Information To be completed by purchaser ☐ Information to be completed by manufacturer	
9 ○ UNITS OF MEASUREMENT 10 ☐ US Customary units 11 ☒ SI units 12 ○ RATING REQUIREMENTS 13 Driven equip. (2.1.4): Norm. _____ Max _____ kW 14 Driver: Rated _____ Max _____ kW 15 Normal transmitted power (2.2.2) _____ kW 16 Gear unit rated power (2.2.1) <u>1620</u> kW 17 Torque @ max cont speed _____ Nm 18 Max torque (2.2.1) _____ Nm @ _____ rpm 19 ☐ Reducer ☒ Increaser 20 Rated speed (2.1.5): 21 Input <u>1800</u> rpm ☐ Specified ☒ Nominal 22 Output <u>10736</u> rpm ☐ Specified ☒ Nominal 23 Allow var in gear ratio (2.1.5) (+) (-) _____ % 24 Max continuous speed (1.5) <u>1800 / 10736</u> rpm 25 Trip speed (1.5) (2.1.7) <u>1980 / 11809,6</u> rpm 26 Gear service factor (2.2.3.1) <u>1,4 API 613/2003 5 TH</u> (min) 27 Hardness (2.2.3.2) Pinion _____ Gear _____ 28 Shaft assembly designation (2.1.10) <u>L/R</u> 29 HS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW 30 LS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW 31 External loads (2.1.16) _____ 32 Other operating conditions (2.2.2) (2.6.1.3) _____	10 ■ BASIC GEAR DATA 11 ☒ Single stage ☐ Single helical 12 ☐ Double stage ☒ Double helical 13 ☐ Epicyclic ☐ <u>horizontal offset</u> 14 Mechanical rating (1.5.16) <u>2268</u> kW @ <u>1800 / 10737,9</u> rpm 15 Gear service factor (2.2.3.1) <u>1,46 API 613/2003 5 TH</u> (actual) 16 Full load gear unit power loss <u>21</u> kW 17 Gear Unit Mechanical efficiency <u>98,70</u> % 18 Rating speed Pinion <u>10.737,9</u> Gear <u>1.800,0</u> rpm 19 Hardness used for 20 Rating, (HB or Rc) Pinion <u>58 HRC</u> Gear <u>58 HRC</u> 21 Tooth pitting index, "K" (2.2.4.1) (2.2.4.2) 22 Allowable <u>2,17</u> Actual <u>2,06</u> MPa 23 Material index number (Fig 3, Table 4) <u>3,03</u> MPa 24 Bending stress number, "S_t" (2.2.5.1) (2.2.5.2) 25 Pinion: Allowable <u>265,4</u> Actual <u>251,0</u> MPa 26 Gear: Allowable <u>265,4</u> Actual <u>238,8</u> MPa 27 Pitch line velocity <u>63,0</u> m/s 28 Anticipated SPL (2.1.6) <u>82</u> dB(A) @ <u>1</u> m 29 WR² referred to LS shaft <u>29,88</u> kgm² 30 Breakaway torque <u>90</u> Nm @ LS Shaft 31 Pinion teeth hardness range <u>58 - 63 HRC</u> 32 Pinion teeth hardening method <u>CARBURIZED</u> 33 ☐ HS shaft separate hardness range _____ 34 Gear teeth (rim) hardness range <u>58 - 63 HRC</u> 35 Gear teeth hardening method <u>CARBURIZED</u> 36 Gear hub: 37 ☒ Forged cylinder ☐ Forged & Capped ☐ Fabricated 38 Gear to Shaft fit method (2.5.3.2) 39 ☐ Integral ☐ Keyed interference ☒ Keyless interference 40 Rim attachment (2.5.3.2) <u>FORGED GEAR WHEEL</u> 41 LS shaft hardness range <u>HB 230 - 274</u> 42 Journal static weight loads (2.6.6.3) 43 Pinion <u>37</u> / <u>4</u> kg Gear <u>347</u> / <u>253</u> kg 44 Total gear unit assembled weight <u>1900</u> kg 45 NOTES: _____ 46 _____ 47 _____ 48 _____ 49 _____ 50 _____
35 ○ INSTALLATION DATA (2.1.14) 36 ☐ Indoor ☐ Heated ☐ Under roof 37 ☒ Outdoor ☐ Unheated ☐ Partial sides 38 ☐ Grade ☐ Mezzanine ☒ ONSHORE 39 ☐ Winterization required ☐ Tropicalization required 40 Electrical area (2.1.10) Class _____ Grp _____ Div _____ 41 Electrical area (2.1.10) Zone <u>2</u> Grp <u>IIA</u> Temp <u>T1</u> °C 42 Max allow SPL (2.1.6) _____ dB(A) @ _____ m 43 Elevation _____ m Barometer _____ kPa abs 44 Range of ambient temperatures: 45 Dry bulb _____ °C Wet bulb _____ °C 46 Normal _____ °C _____ °C 47 Maximum <u>82</u> °C _____ °C 48 Minimum <u>0</u> °C _____ °C 49 Unusual conditions ☐ Dust ☐ Fumes 50 ☐ _____	

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No.	41104	Item No.	B
P.O. No.		Date	
Requisition No.			
Inquiry No.			
Revision	1	Date	06.03.2015 By HNI

■ GEAR DATA				○ COUPLINGS AND GUARDS			
	Pinion	Gear		Pinion	Gear		
Number of teeth	29	173		Coupling furnished by (3.2.1)	Compr. Supplier	Compr. Supplier	
Gear ratio	5,97			Mount coupling halves (3.2.2)	Compr. Supplier	Compr. Supplier	
Tangential load, "Wt" (2.2.4.2)	25.731	N		Cplg. guard adapter by (3.2.3)	Gear Supplier	Gear Supplier	
AGMA Geometry factor "J"	0,52	0,54		Cplg. guard furnished by (3.2.3)	Compr. Supplier	Compr. Supplier	
Pitch diameter	111,98	668,02	mm	Coupling vendor (3.2.3)			
Outside diameter	120,30	673,50	mm	Vendor's model number (3.2.3)			
Root diameter	103,05	656,32	mm	Coupling weight on shaft, kg	10,4	26,4	
Center groove diameter	93,00	640,00	mm	CG Inboard / outboard of shaft end	Outboard	Outboard	
Normal pressure angle	20,00	deg		Hub drill template provided	☐	☐	
Normal diametral pitch	7,26	in ⁻¹		■ SHAFT END DETAIL (2.5.4.2)			
Helix angle	24,25	deg		Shaft end detail specified by: ☒ Purchaser ☐ Gear vendor			
Center distance	390,00	mm		(Integral unless otherwise specified)			
Backlash min	0,28	mm		Shaft end detail if 'otherwise' specified: Pinion Gear			
Net face width, "Fw"	130,00	mm		Tapered / Keyless ☐ ☐ ☐ ☐			
Pinion L/D	1,74			Tapered / 1-Key ☐ ☐ ☐ ☐			
Face overlap ratio	4,86			Tapered / 2-Keys ☐ ☐ ☐ ☐			
Transverse contact ratio	1,45			Cylindrical / 1-Key ☐ ☐ ☐ ☐			
AGMA 6011 service factor	2,87			Cylindrical / 2-Keys ☐ ☐ ☐ ☐			
Rating based on ANSI/AGMA 6011 with SF=1,0				Other ☒ Flanged ☐ ☐ ☐			
Durability Power	5404	kW		Shaft diameter 75,0 120,0 mm			
Strength Power	4652	kW		(If integral flange use diameter immediately adjacent to flange)			
Tooth Surface Finish, Ra	0,4	0,4	µm	■ RADIAL BEARINGS			
Tooth Generation Process	Hobbing	Hobbing		Pinion Gear			
Tooth Finishing Process	Grinding	Grinding		Type T.PADS / T.PADS CYL. / CYL.			
Lead modification (2.2.4.6) ☒ Not Req'd ☐ Req'd				Diameter 80 / 80 120 / 120 mm			
Calculated Total Lead Mismatch		µm		Length 56 / 56 60 / 60 mm			
■ SCUFFING DATA (2.2.6)				Journal velocity 45,0 / 45,0 11,3 / 11,3 m/s			
Scuffing Data per ANSI/AGMA 925-A03				Loading 3,08 / 3,10 2,52 / 2,26 N/mm ²			
Scuffing Risk (2.2.6) <=5% (Low) Calculation Method AGMA925				Clearance (min-max) mm			
Composite surface roughness, ox 0,57 µm				Span 340 340 mm			
Specific film thickness, EHL Amin 2,54 µm				Power loss each bearing 6,3 / 6,3 0,7 / 0,7 kW			
Tooth temperature, 0m 80 °C				Oil flow each bearing 15,0 / 15,0 5,0 / 5,0 l/min			
Maximum contact temperature, 0Bmax 93 °C				■ THRUST BEARINGS			
■ MATERIALS				Location OPP.CPLG.SIDE			
Gear casing Steel Oil seals aluminum				Manufacturer FLENDER FLENDER			
Pinion(s) 18CrNiMo7-6				Type NO COMB.TAP.LANDS			
Gear rim(s) 18CrNiMo7-6				Size BPK LEG 4"			
HS Shaft Integral LS Shaft 42CrMo4				Area 5160 mm ²			
Radial bearings Babbit Backing Steel				Loading 1,35 MPa			
Thrust bearing(s) Babbit Backing Steel				Rating 1,50 MPa			
○ SHAFT END DETAIL				Int. thrust load N			
☒ Gear shaft end for coupling integral flange (2.5.4.2)				Ext. thrust load 2.700 N			
☒ Pinion shaft end for coupling integral flange (2.5.4.2)				Power loss each 0,0 5,0 kW			
☒ Other : WITHOUT BOLTS				Oil flow each bearing 0,0 15,0 l/min			
				NOTES :			

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

1 ○ LUBRICATION REQUIREMENTS 2 ☐ Oil system furnished by (2.8.3) _____ 3 ☐ Other _____ ☐ Gear vendor _____ 4 ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) 5 ☐ ISO Grade _____ Load stage (2.2.6) 7,0 6 7 ■ MESH 8 Mesh and windage power loss 2,0 kW 9 Oil flow, mesh 9,0 l/min 10 11 ■ LUBRICATION REQUIREMENTS 12 Min. startup oil temperature 20,0 °C 13 Normal oil inlet temperature 60,0 °C 14 Maximum oil inlet temperature 65,0 °C 15 Unit oil flow (total) 64,0 l/min 16 Unit oil pressure 2,5 bar 17 ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) 18 ☐ ISO Grade 46 Load stage (2.2.6) 7,0 19 20 ■ PIPING CONNECTIONS <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Service</th> <th>No.</th> <th>Size</th> <th>Type</th> </tr> <tr> <td>Lube oil inlet</td> <td>1</td> <td>1,5 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Lube oil outlet</td> <td>1</td> <td>6 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing drain *</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Vent</td> <td>1</td> <td>1,5 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing purge</td> <td></td> <td></td> <td></td> </tr> </table> 27 * Casing drain is 'dead bottom' housing drain, not lube oil outlet 28 ○ MOUNTING PLATES 29 ☐ Gear furnished with (3.3.1.1) 30 ☐ Baseplate ☐ Soleplate ☐ Subplate(s) (3.3.2.10) 31 ☐ Mounting plates(s) furnished by (3.3.1.1) _____ 32 ☐ Baseplate leveling (3.3.2.3) _____ 33 ☐ Baseplate with leveling pads (3.3.2.3) 34 ☐ Baseplate suitable for column mounting (3.3.2.4) 35 ☐ Vendor review of purchaser's foundation dwgs. (2.1.13) 36 ☐ Grout type (3.3.1.2.4) _____ 37 38 ○ CONTRACT DATA 39 ☐ Test data prior to shipment _____ 40 ☒ Progress report (5.3.3) _____ 41 ☐ Vendor signoff of inspector checklist (4.1.1.3) 42 ☒ Information retained for 20 years (4.2.1.1) (4.2.2.6.1) 43 ☐ Technical manual (5.3.6.4) 44 ☒ PAINTING (4.4.3.1) ☒ Flender standard RAL5015 (blue) 45 ☒ Painting housing interior not allowed (2.3.1.14) 46 ○ SHIPMENT 47 ☐ Steel rotor storage container (4.4.5) ☐ Shaft covers (4.4.4) 48 <table style="width:100%;"><tr><td></td><td>Contract unit</td><td>Spares</td></tr><tr><td>Export boxing</td><td>☐</td><td>☐</td></tr><tr><td>Domestic boxing</td><td>☐</td><td>☐</td></tr><tr><td>Outdoor storage over 6 mos.</td><td>☐</td><td>3 years indoor ☐ (4.4.3.9)</td></tr></table>	Service	No.	Size	Type	Lube oil inlet	1	1,5 in.	ANSI 150 LBS	Lube oil outlet	1	6 in.	ANSI 150 LBS	Casing drain *				Vent	1	1,5 in.	ANSI 150 LBS	Casing purge					Contract unit	Spares	Export boxing	☐	☐	Domestic boxing	☐	☐	Outdoor storage over 6 mos.	☐	3 years indoor ☐ (4.4.3.9)	Job No. 41104 Item No. B P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision 1 Date 08.03.2015 By HNI ○ ADDITIONAL REQUIREMENTS ○ VIBRATION DETECTORS RADIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 8 ☒ X-Y probes pinion bearings ☒ Coupling end ☒ Blind end ☒ X-Y probes gear bearings ☒ Coupling end ☒ Blind end ☐ Other _____ AXIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 2 ☐ Dual probes at each thrust bearing ☐ Single probe any shaft without thrust bearing ☐ Other _____ ONE EVENT PER REVOLUTION PROBE (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA Total No. 2 ☒ One on input shaft ☒ One on output shaft ☐ Other _____ ACCELEROMETER (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ No. required 2 ☒ Pinion coupling end ☒ Gear coupling end ☐ Other _____ ○ TEMPERATURE DETECTORS ☐ Dial type thermometers (3.4.2.7) _____ ☒ Type brg. temp. sensors (3.4.2.7) (2.7.1.3) PT100 ☐ RTD ☐ Thermocouple / ☐ Simplex ☒ Duplex Calibration Yes ☒ HSALS bearings no. sensors each 2 / 2 ☒ Thrust number of sensing elements each face 2 ○ OTHER VIBRATION AND TEMPERATURE (3.4.2.5) (3.4.2.6) Other Gear vendor Oscillator demodulator supplied by ☐ ☒ Vibration monitor supplied by ☒ ☐ ☐ Vibration shutdown delay time _____ seconds Temperature monitor supplied by ☒ ☐ Oscillator demodulator J-box by ☒ ☐ Temp. sensor termination J-box by ☒ ☐ J-box type _____ Mount _____ ○ MISCELLANEOUS ☒ Undamped critical analysis report (2.6.2.1) ☐ w/ dampd rotr resps analys rpt (2.6.2.4.3) (2.6.2.6) Torsional analysis by (2.6.5.2) ☐ Gear vendor ☒ Other ☒ Spare set of gear rotors (4.3.2.4) ☐ Gear case furnished with inlet purge connection (2.4.3) ☐ Orientation of oil inlet & drain conns. (2.4.6) ☒ Filter breather location (2.3.1.12) Prov. on upper casing ☐ Torsional device provisions (2.5.4.5) ☐ Rotor vertical storage provisions (2.5.4.8) ☐ Rotor vertical storage fixture(s) (3.6.2) ☐ Vendor service rep. on site (2.1.13)
Service	No.	Size	Type																																		
Lube oil inlet	1	1,5 in.	ANSI 150 LBS																																		
Lube oil outlet	1	6 in.	ANSI 150 LBS																																		
Casing drain *																																					
Vent	1	1,5 in.	ANSI 150 LBS																																		
Casing purge																																					
	Contract unit	Spares																																			
Export boxing	☐	☐																																			
Domestic boxing	☐	☐																																			
Outdoor storage over 6 mos.	☐	3 years indoor ☐ (4.4.3.9)																																			

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No. 41104 Item No. B
P.O. No. _____ Date _____
Requisition No. _____
Inquiry No. _____
Revision 1 Date 06.03.2015 By HNI

O INSPECTIONS AND TESTS (4.1)				
	Req'd	Witness	Observe	Test Log
☐ Advance notice of witness testing required (4.1.3)				
Number calendar days _____				
Shop Inspection (4.1.1)	☐	☐	☐	
Cleanliness Inspection (4.2.3.1)	☐	☐	☐	
Hardness Verification (4.2.3.3)	☒	☐	☐	☒
Dismantle-reassembly (4.3.2.3.1)	☒	☐	☐	☐
Contact Check (2.5.2.2)	☒	☐	☐	☐
Contact Check Tape Lift (2.5.2.2)	☒	☐	☐	☒
Gear accuracy check (2.5.2.1)	☒	☐	☐	☐
Double helical axial stability (2.5.2.3)	☒	☐	☐	☒
Special testing integral forged gears (2.5.3.3)				
(testing per mutual agreement)	☐	☐	☐	☐
Residual unbalance check (2.6.6.2)	☒	☐	☐	☒
Mechanical Run Test (Main) (4.3.2)	☒	☐	☐	☒
Mechanical Run Test (Spare) (4.3.2.4)	☐	☐	☐	☐
Add'l. Mechanical Tests (4.3.2.2.16)	☐	☐	☐	☐
Part or Full Load And Full Speed				
Test (4.3.3.1)	☐	☐	☐	☐
Full torque, reduced speed (4.3.3.2)	☐	☐	☐	☐
Full Torque Static Test (4.3.3.3)	☐	☐	☐	☐
Back-To-Back Locked Torque				
Test (4.3.3.4)	☐	☐	☐	☐
Sound Level Test (4.3.3.5)	☒	☐	☐	☒
Additional gear tooth test (4.2.2.8)	☐	☐	☐	☐
Use shop Lube System	☒	☐	☐	
Use job lube system	☐	☐	☐	
Use shop Vibration Probes, Etc.	☐	☐	☐	
Use job Vibration Probes, Etc.	☒	☐	☐	
Final Assembly, Maintenance &				
Running Clearance (4.2.1.1.e)	☒	☐	☐	☒
Oil System Cleanliness (4.2.3.2)	☐	☐	☐	
Oil System-Casing Joint				
Tightness (4.3.2.1.4)	☐	☐	☐	
Warning And Protection				
Devices (4.3.2.1.5)	☐	☐	☐	
Seismic Vibration Data (4.3.2.2.3)	☐	☐	☐	☐
Vibration, Phase Plots (4.3.2.2.12)	☒	☐	☐	☒
Oil Inlet Range test (4.3.2.2.13)	☐	☐	☐	☐
Tape recorded Vibration Data	☒	☐	☐	☒
(4.3.2.2.14) (4.3.2.2.15)	☐			
Purchaser copy				
NON-DESTRUCTIVE TESTING (4.2.1.2) (4.2.2.1)				
	Surface	Sub surface		Log
☐ Casing	☐	☐		☐
☒ Rot. Elmts.	☒	☒		☒
☒ Bearings	☒	☒		☒
☐ Other :	☐	☐		☐
(Specify)				

NOTES : _____

During start-up, gears can exhibit a transient spike reading of vibration levels that will exceed shutdown settings. Therefore a trip multiplier is recommended in the control system.

Mechanical running test duration 4 hours including



- Shaft vibration record using job vibration probes if ordered
- Bearings temperature records
- Casing vibration measurement
- Sound level pressure measurement
- Power losses measurement at oil outlet
- Performed with oil ISO VG 32

Oil flow requirement and power losses are calculated values only, add normal safety margins for sizing heat exchangers.



Positive direction of external

APPAREILS _ Edition du :06.03.2015
1/1



ADDITIONAL TECHNICAL DATASHEET				Job No. <u>41104</u> Item No. <u>B</u> P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision <u>1</u> Date <u>06.03.2015</u> By <u>HNI</u>																																													
☒ ADDITIONAL GEAR DATA				☐ TURNING GEAR (Dimensioning is preliminary I)																																													
<i>Efficiency</i>				<i>Calculation results</i>																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Percent of rated power</th> <th style="width: 50%;">Efficiency</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">100%</td> <td style="text-align: center;">98,70</td> </tr> <tr> <td style="text-align: center;">75%</td> <td style="text-align: center;">98,66</td> </tr> <tr> <td style="text-align: center;">50%</td> <td style="text-align: center;">98,38</td> </tr> <tr> <td style="text-align: center;">25%</td> <td style="text-align: center;">97,42</td> </tr> <tr> <td style="text-align: center;">10%</td> <td style="text-align: center;">87,68</td> </tr> </tbody> </table>				Percent of rated power	Efficiency	100%	98,70	75%	98,66	50%	98,38	25%	97,42	10%	87,68	Required turning speed _____ rpm Actual turning speed _____ rpm Required breakaway torque _____ Nm Actual breakaway torque _____ Nm Actual maximum torque _____ Nm Actual acceleration time _____ s																																	
Percent of rated power	Efficiency																																																
100%	98,70																																																
75%	98,66																																																
50%	98,38																																																
25%	97,42																																																
10%	87,68																																																
<i>Losses</i>				<i>Motor</i>																																													
Power loss at no load _____ kW Heat rejection _____ kcal/h				Supplier _____ Power _____ kW Voltage _____ V Frequency _____ Hz Speed _____ rpm Electric standard _____																																													
☐ PUMP DETAILS (Dimensioning is preliminary I)				<i>Turning gear</i>																																													
Design : _____ Speed : _____ rpm Oil flow : _____ l/min Oil pressure : _____ bar NPSH : _____ m Safety valve : _____ Driving method : _____ Material : _____ Flanges : _____ Testing : _____ Furniture of ATEX certificate : _____				Type _____ Ratio _____																																													
				<i>Clutch</i>																																													
				Type _____ Max. allowable torque _____ Nm																																													
				<i>Miscellaneous</i>																																													
				Starting device _____ Switch details _____																																													
☒ INSTRUMENTATION PACKAGE																																																	
<i>Thermometer</i>				<i>Thermoelements</i>																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> </thead> <tbody> <tr> <td>Qty</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Type</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>					Bearing	Thrust bearing	Oil inlet/outlet	Qty				Type				<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> </thead> <tbody> <tr> <td>Type</td> <td>DUPLEX 2x3F</td> <td>DUPLEX 2x3F</td> <td></td> </tr> <tr> <td>Classification</td> <td>IEC60751</td> <td>IEC60751</td> <td></td> </tr> <tr> <td>Removable from the outside</td> <td>NO</td> <td>NO</td> <td></td> </tr> <tr> <td>ATEX</td> <td>ATEX Eexia</td> <td>ATEX Eexia</td> <td></td> </tr> </tbody> </table>					Bearing	Thrust bearing	Oil inlet/outlet	Type	DUPLEX 2x3F	DUPLEX 2x3F		Classification	IEC60751	IEC60751		Removable from the outside	NO	NO		ATEX	ATEX Eexia	ATEX Eexia											
	Bearing	Thrust bearing	Oil inlet/outlet																																														
Qty																																																	
Type																																																	
	Bearing	Thrust bearing	Oil inlet/outlet																																														
Type	DUPLEX 2x3F	DUPLEX 2x3F																																															
Classification	IEC60751	IEC60751																																															
Removable from the outside	NO	NO																																															
ATEX	ATEX Eexia	ATEX Eexia																																															
<i>Shaft vibrations</i>																																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 25%;">Radial</th> <th style="width: 10%;">HS</th> <th style="width: 10%;">Axial</th> <th style="width: 10%;">Keyphasor</th> <th style="width: 10%;">Accelerometer</th> </tr> </thead> <tbody> <tr> <td>Type</td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td>LS</td> <td>No</td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td>ACCELEROMETER BENTLY</td> </tr> <tr> <td>Probe</td> <td>Yes</td> <td>LS</td> <td>No</td> <td>Yes</td> <td></td> </tr> <tr> <td>Proximitior</td> <td>Yes</td> <td>LS</td> <td>Yes</td> <td>Yes</td> <td></td> </tr> <tr> <td>Probe holder</td> <td>Yes</td> <td>LS</td> <td>Yes</td> <td>Yes</td> <td></td> </tr> <tr> <td>Connection head</td> <td>Yes</td> <td>LS</td> <td>No</td> <td>Yes</td> <td></td> </tr> <tr> <td>mounting kit</td> <td></td> <td>LS</td> <td>Yes</td> <td></td> <td>Yes</td> </tr> </tbody> </table>									Radial	HS	Axial	Keyphasor	Accelerometer	Type	B.N. 3300 XL 8mm Sys. 9M	LS	No	B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY	Probe	Yes	LS	No	Yes		Proximitior	Yes	LS	Yes	Yes		Probe holder	Yes	LS	Yes	Yes		Connection head	Yes	LS	No	Yes		mounting kit		LS	Yes		Yes
	Radial	HS	Axial	Keyphasor	Accelerometer																																												
Type	B.N. 3300 XL 8mm Sys. 9M	LS	No	B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY																																												
Probe	Yes	LS	No	Yes																																													
Proximitior	Yes	LS	Yes	Yes																																													
Probe holder	Yes	LS	Yes	Yes																																													
Connection head	Yes	LS	No	Yes																																													
mounting kit		LS	Yes		Yes																																												
<i>Junction box(es)</i>				<i>Miscellaneous</i>																																													
Qty <u>0</u> Manufacturer _____ Material _____ ATEX <u>None</u>				Identification ☒ wire ☒ conduit ☐ junction box Conduit type _____ Transmitter type _____ Qty _____ Terminal block type _____ Qty _____																																													

Commercial Conditions

- Prices are quoted FCA Illkirch-Graffenstaden following Incoterms 2010 including packing cat 1A of SEI, 1999 issue, ind. 2.
- Progress payments : 100% at delivery.
- This quotation is subjected to the Flender Graffenstaden Standard Terms and Conditions of Sales and valid for acceptance until the 15th of July 2015.
- Where approval of drawings is required, approval must be in line with the document schedule.
- Warranty period is 18 months of operation or 24 months after delivery whichever occurs first. We recommend the supervision of our engineer for the commissioning.
- Flender-Graffenstaden SAS shall not be obligated to fulfill this agreement if such fulfillment is prevented by any impediments arising out of national or international foreign trade or customs requirements or any embargoes or other sanctions.


Applicable documents for the quotation (available on demands)

Documents schedule,
Quality plan
Painting standard,
Standard Terms and Conditions of Sales

We thank you for the opportunity of quoting and look forward to the pleasure of serving you.

Very truly yours,

N. HOST
(Project Engineer)



Y. FRIEDMANN
(Sales Manager)



Generated with CAMEC V 4.9.5 26 Feb 2014

**** "This quotation is subject to confidentiality. Information thereof may not be shared with or forwarded to any third parties!"**